

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
1 May 2003 (01.05.2003)

PCT

(10) International Publication Number
WO 03/035496 A1

(51) International Patent Classification: **B65D 19/38**,
19/32

(74) Agent: **DIAMOND, Konstantine, J.**; Rehrig Pacific
Company, 4010 East 26th Street, Los Angeles, CA 90023
(US).

(21) International Application Number: PCT/US02/33292

(22) International Filing Date: 18 October 2002 (18.10.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
10/040,098 19 October 2001 (19.10.2001) US

(71) Applicant (for all designated States except US): **REHRIG
PACIFIC COMPANY** [US/US]; 4010 East 26th Street,
Los Angeles, CA 90023 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG,
SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ,
VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK,
TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

(72) Inventor; and


(75) Inventor/Applicant (for US only): **APPS, William, P.**
[US/US]; 225 Lake Heights Drive, Alpharetta, GA 30022
(US).

Published:

— with international search report

[Continued on next page]

(54) Title: PALLET ASSEMBLY WITH FIRE RETARDANT PROPERTIES



(57) Abstract: A pallet assembly (410) includes a top deck (412) having a top deck upper surface and a top deck lower surface and also having a first predetermined fire retardancy. A bottom deck (414) having a bottom deck upper surface and a bottom deck lower surface, and also having a second predetermined fire retardancy and a column (428) extending between the top deck and bottom deck, the column having an other fire retardancy lower than at least one of the first and second fire retardancies.

WO 03/035496 A1

WO 03/035496 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

PALLET ASSEMBLY WITH FIRE RETARDANT PROPERTIES

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a pallet assembly.

5 2. Background Art

Pallets formed of molded plastic material have distinct advantages over those made of wood or metal. While wood pallets have sufficient stiffness, they are heavy; are subject to warpage, splintering and splitting; are nonuniform in strength; and gain significant weight when wet. Metallic pallets typically are
10 expensive and, in the case of steel, heavy and subject to corrosion. Plastic pallets are stronger, lighter and more durable than wooden pallets. Heretofore, fire retardance as it relates to plastic pallets has not been recognized as an issue. However, recently, plastic pallets have been the subject of standards promulgated by the National Fire Protection Association (NFPA), Underwriters Laboratories Inc.
15 (UL), Factory Mutual Research Company (FMRC), and National Association of Fire Marshals.

Some standards allow for plastic pallets to be used the same as wood pallets when experimental data show equivalency in the burning and suppression characteristics between the plastic and wood pallets. Unfortunately, some material
20 presently used to help promote fire retardance in plastic pallets, such as an engineered resin blend of high-impact polystyrene and polyphenylene oxide, is very expensive and thus not cost efficient to mold an entire pallet from this material. Such material may also not be as injection-molding friendly as other polymeric materials.

Therefore, a pallet is desired which is accepted by the fire community as having burn and suppression properties substantially similar or better than wood, is relatively inexpensive, lightweight, and easy to manufacture.

SUMMARY OF THE INVENTION

5 It is an object according to the present invention to provide a pallet which is desired which is accepted by the fire community as having burn properties equivalent to wood.

 It is another object according to the present invention to provide a pallet which as the desired level of stiffness, is relatively inexpensive, lightweight, and
10 easy to manufacture.

 It is another object according to the present invention to provide a multi-component pallet which allows for the freedom to allocate different materials among the various components to achieve desired properties and characteristics.

 In accordance with the objects of the present invention, provided is a pallet
15 assembly includes a top deck having a top deck upper surface and a top deck lower surface and also having a first predetermined fire retardancy. A bottom deck having a bottom deck upper surface and a bottom deck lower surface, and also having a second predetermined fire retardancy. A column extending between the top deck and bottom deck, the column having an other fire retardancy lower than at least one
20 of the first and second fire retardancies.

 In another embodiment, a pallet assembly includes a first deck member and a second deck member mounted to the first deck member, the second deck member having a first predetermined fire retardancy. A third deck member spaced from the second deck member and a fourth deck member mounted to the third deck member,
25 the fourth deck member having a second predetermined fire retardancy. At least one column member extends between the second and third deck members, and having a third predetermined fire retardancy lower than that of the second and fourth decks.

The third deck member may have a fire retardancy substantially equivalent to that of the at least one column member. Further, at least one elongated reinforcement member may extend within at least one of the top and bottom decks. Also, the top member and mid-top member may have mating ribbed surfaces which are attached to each other, and the bottom member and mid-bottom member have mating ribbed surfaces which are attached to each other.

In another embodiment, provided is a pallet assembly having a first deck member and a second deck member mounted to the first deck member, the second deck member having a predetermined fire retardancy. Also provided is a third deck member spaced from the second deck member and a fourth deck member mounted to the third deck member. It also includes at least one column member extending between the second and third deck members and attached thereto. The first deck member, third deck member, fourth deck member and the at least one column member each has an other predetermined fire retardancy which is less than that of the second deck member.

Another embodiment is directed to a pallet assembly having a horizontally-disposed first portion formed of a polymeric material and having a first top surface and a first bottom surface, the first portion having a first predetermined fire retardancy. Also included is a horizontally-disposed second portion formed of a polymeric material and having a second top surface and a second bottom surface, the second portion having a second predetermined fire retardancy. It further includes at least one vertically-disposed portion extending between the first portion and second portion and having an other predetermined fire retardancy less than that of the first and second portions. The first portion is a pallet top deck, the second portion is a pallet bottom deck, and the vertically-disposed portion is a column.

The above objects and other objects, features, and advantages of the present invention are readily apparent from the following detailed description of the best mode for carrying out the invention when taken in connection with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIGURE 1 is a perspective view of a first embodiment of a pallet assembly according to the present invention; and

FIGURE 2 is an exploded perspective view of Figure 1;

5 FIGURES 2a, 2b, and 2c are alternate exploded views of Figure 1; and

FIGURE 3 is an exploded cross-sectional view of an alternate embodiment according to the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT(S)

10 A pallet assembly according to the present invention is illustrated in Figures 1-2 as pallet assembly 410. Pallet assembly 410 includes the following: a top deck 412 having a top portion 430 and a mid-top portion 432; a bottom deck 414 having a mid-bottom portion 434 and a bottom portion 436; and a plurality of column members 428.

15 While pallet assembly 410 may be used in the same environments as other pallets disclosed herein, it is particularly well-suited to a pallet assembly which seeks to enhance the properties of its individual components, and doing so in a cost efficient manner when feasible. For example, due to their positioning within pallet 410, column members 428 are subject to repeated impact by fork lift tines. Thus,
20 in a preferred embodiment, columns 428 may be molded from a plastic material or composite that provides high impact resistance. Upper and lower decks 412, 414 on the other hand may not require a high impact resistant material, but instead may be formed of a material that has relatively high friction coefficient, high stiffness, high fire retardant characteristics (one which improves the burning and suppression
25 characteristics) properties of the pallet.

With regard to the burn and suppression characteristics of a pallet, the present invention teaches that the horizontal portions of a pallet (i.e. the decks), and

particularly the underside of the decks, have a greater exposure to flame during burn as flames are traveling upwards, and thus have a relatively greater influence on the pallet burn rate than the vertical portions of a pallet (i.e. the columns). Accordingly, for a pallet seeking to incorporate fire retardant material into its design in an effective and cost efficient manner, it is unexpectedly taught herein that the entire pallet does not need to be formed of fire retardant material, but instead selected components may be formed thereof. One embodiment according to the present invention teaches that the horizontal portions of the pallet have a predetermined level of fire retardance, while the vertical portions have minimal or no fire retardance, and in any event less than the horizontal portions. Thus, in keeping with these teachings, the decks 412, 414 (the horizontal surfaces) of pallet 410 are formed of a polymeric material having fire retardant properties, typically by including a fire retardant resin or additive to a plastic carrier, thereby defining a predetermined level of fire retardance. On the other hand, the columns 428 (the vertical surfaces) may be formed separately from a high impact material or other type of polymer material which also has little or no flame retardance, and thus has a predetermined level of flame retardant which is less than decks 412, 414.

More particularly, for one deck pallets and two deck pallets, the present invention further teaches that the upper horizontal portion of a pallet (i.e. the top deck components) has the greatest affect on the burn rate of a pallet than the other portions of the pallet. Accordingly, in keeping with the teachings according to the present invention, top deck 412 of pallet 410 is formed of a plastic material having a predetermined level of flame retardance, while the columns 428 and lower horizontal surfaces (the bottom deck 414) may be formed separately from a high impact material or other type of polymer material which has little or no flame retardant material, and in any event has less than top deck 412. In such an embodiment, the columns may be integrally formed with the bottom deck of the same material (Figure 3).

In a pallet having multiple deck portions, the present invention further teaches that the horizontal lower portion of each deck has a greater affect on the burn and suppression rate of a pallet than the other deck portions and column portions. Thus, in a preferred embodiment, mid-top portion 432 and bottom portion

436 of pallet 410 are formed of a plastic material each having a predetermined level of flame retardance which is higher than that of the remaining components of the pallet. Again, the remaining components may be little or no fire retardance properties.

5 Even more particularly for pallets having multiple deck portions, in a more preferred embodiment, it is taught herein that the horizontal lower portion of the top deck has the greatest affect on the burn rate of a pallet and therefore requires a higher level of fire suppression than the other pallet components. Accordingly, mid-top portion 432 has a predetermined level of flame retardance which is higher than
10 that of the remaining components of the pallet. In such an embodiment, the columns may be integrally formed with the mid-bottom deck portion of the same material (Figure 3).

Pallet assembly 410 may also include reinforcement members therein.
15 Bottom deck 414 includes a cross-reinforcement member 450 and peripheral reinforcement members 452, 454, 456, 458. Top deck 412 includes a cross-reinforcement member 460 which lies in a plane parallel to but along an axis perpendicular to that of reinforcement member 450.

Joining the pallet components to each other may be performed by means
20 known to those in the art. For example, the columns may be press fit into the decks, or may be snapped together into the decks by a snap attachment (one type is shown in U.S. Patent No. 6,006,677). The parts may also be welded via a welding for dissimilar materials.

Thus, this pallet embodiment allows only those desired components to be
25 formed from a fire retardant material, such that the pallet may have the desired fire retardant, and burn and suppression characteristics. This pallet also allows the manufacturer the freedom to selectively control and allocate the material and/or amount of fire retardant additive in each component. Accordingly, this provides a lower cost pallet, since the entire pallet no longer needs to be formed of a single
30 material, particularly a more costly single fire retardant material. Accordingly, the desired fire retardant levels for each pallet component and for the overall pallet may

b achieved for obtaining desired pallet burn and suppression characteristics in a cost efficient manner, so that the pallet disclosed herein may meet the industry specifications, such as those outlined by, and including but not limited to, NFPA 13, FMRC 4995, and UL 2335, incorporated herein by reference. Thus, the fire retardant additives may be adjusted such that the pallet as a whole meets the desired guidelines. Particularly, the burn and suppression characteristics should be substantially equivalent or better than a similarly sized wood pallet, such as one made from hard wood. Accordingly, the pallet should have a fire rating and burn rate no higher than wood. The particular materials used may be those known in the art for producing fire retardant characteristics in pallets, including but not limited to commodity items, such as polymer resins like polyolefins having a halogen based flame retardant resin additive.

Of course, as illustrated herein, these teachings are applicable to pallets of any size, design, and to those manufactured by various processes. By way of example and not limitation, the teachings herein may also apply to reinforced pallets (Figure 2) or to pallets without additional reinforcement in the top and/or bottom decks (Figures 2a, 2b, 2c). The teachings may also apply to pallets having internal ribbing, cross-ribbing, and box-beams 492a,b (Figure 3), or to pallets without (Figure 2c). They are applicable to one deck pallets, two deck pallets, and pallets formed from multiple deck portions. Because some fire retardant additives may cause some polymer carriers to lose some stiffness, the teachings herein are particularly applicable to reinforced pallets.

While embodiments of the invention have been illustrated and described, it is not intended that these embodiments illustrate and describe all possible forms of the invention. Rather, the words used in the specification are words of description rather than limitation, and it is understood that various changes may be made without departing from the spirit and scope of the invention.

WHAT IS CLAIMED IS:

1. A pallet assembly comprising:
a first deck member;
a second deck member mounted to the first deck member, the second deck member having a first predetermined fire retardancy;
a third deck member spaced from the second deck member;
a fourth deck member mounted to the third deck member, the fourth deck member having a second predetermined fire retardancy; and
at least one column member extending between the second and third deck members, the at least one column having a third predetermined fire retardancy lower than that of the second and fourth decks.
2. The pallet assembly of claim 1 wherein the at least one column member has a first end and a second end, the first end mounted to the second deck member, and the second end mounted to the third deck member.
3. The pallet assembly of claim 1 wherein the first deck member has an other predetermined fire retardancy less than that of the second deck member.
4. The pallet assembly of claim 1 wherein the third deck member has an other predetermined fire retardancy less than that of the second deck member.
5. The pallet assembly of claim 1 wherein the third deck member has a fire retardancy substantially equivalent to that of the at least one column member.
6. The pallet assembly of claim 1, further comprising at least one elongated reinforcement member extending within at least one of the top and bottom decks.
7. The pallet assembly of claim 1, wherein the top member and mid-top member have mating ribbed surfaces which are attached to each other.
8. The pallet assembly of claim 1, wherein the bottom member and mid-bottom member have mating ribbed surfaces which are attached to each other.

9. A pallet assembly comprising:
a top deck having a top deck upper surface and a top deck lower surface, the top deck having a first predetermined fire retardancy;
a bottom deck having a bottom deck upper surface and a bottom deck lower surface, the bottom deck spaced apart from the top deck and having a second predetermined fire retardancy; and
at least one column extending between the top deck and bottom deck, the at least one column having an other fire retardancy lower than at least one of the first and second fire retardancies.
10. The pallet assembly of claim 9, further comprising at least one elongated reinforcement member extending within at least one of the top and bottom decks.
11. The pallet assembly of claim 9, wherein the top deck comprises a top member and a mid-top member which are joined together.
12. The pallet assembly of claim 11, wherein the top member and mid-top member have mating ribbed surfaces which are attached to each other.
13. The pallet assembly of claim 11, wherein the bottom deck comprises a bottom member and a mid-bottom member.
14. The pallet assembly of claim 13, wherein the bottom member and mid-bottom member have mating ribbed surfaces which are attached to each other.
15. The pallet assembly of claim 9, wherein the top deck has a plurality of box beam sections disposed therein between the top deck upper surface and the top deck lower surface.
16. The pallet assembly of claim 9, wherein the bottom deck has a plurality of box beam sections disposed therein between the bottom deck upper surface and the bottom deck lower surface.

17. A pallet assembly comprising:
a first deck member;
a second deck member mounted to the first deck member, the second deck member having a predetermined fire retardancy;
a third deck member spaced from the second deck member;
a fourth deck member mounted to the third deck member; and
at least one column member extending between the second and third deck members and attached thereto,
wherein the first deck member, third deck member, fourth deck member and the at least one column member each has an other predetermined fire retardancy which is less than that of the second deck member.

18. The pallet assembly of claim 17 wherein the at least one column member has a first column end and a second column end, the first column end mounted to the second deck member, and the second column end mounted to the third deck member.

19. The pallet assembly of claim 17, further comprising at least one elongated reinforcement member extending within at least one of the top and bottom decks.

20. The pallet assembly of claim 17, wherein the top member and mid-top member have mating ribbed surfaces which are attached to each other.

21. The pallet assembly of claim 17, wherein the bottom member and mid-bottom member have mating ribbed surfaces which are attached to each other.

22. A pallet assembly comprising:
a horizontally-disposed first portion formed of a polymeric material and having a first top surface and a first bottom surface, the first portion having a first predetermined fire retardancy;
a horizontally-disposed second portion formed of a polymeric material and having a second top surface and a second bottom surface, the second portion having a second predetermined fire retardancy;

at least one vertically-disposed portion extending between the first portion and second portion and having an other predetermined fire retardancy less than that of the first and second portions.

23. The pallet assembly of claim 22, wherein the first portion is a pallet top deck, the second portion is a pallet bottom deck, and the vertically-disposed portion is a column.







Fig. 1










Fig. 2c




Fig. 3

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/US 02/33292

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 B65D19/38 B65D19/32

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 B65D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 2001/029874 A1 (MUIRHEAD) 18 October 2001 (2001-10-18) paragraph '0010! paragraph '0026! paragraph '0058! paragraph '0059! paragraph '0070! paragraph '0081! paragraph '0082!; figures 1-11 -----	1,9,17, 22
A	US 2001/031807 A1 (ADEDEJI) 18 October 2001 (2001-10-18) paragraph '0015! - paragraph '0024! -----	1,9,17, 22
A	WO 00 01588 A (REHRIG) 13 January 2000 (2000-01-13) figures 1-5 -----	1,9,17, 22



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents:

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

G document member of the same patent family

Date of the actual completion of the international search

4 February 2003

Date of mailing of the international search report

13/02/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Martens, L

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 02/33292

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2001029874 A1	18-10-2001	NONE	
US 2001031807 A1	18-10-2001	AU 5702499 A CA 2345998 A1 EP 1123345 A1 JP 2002526622 T WO 0020495 A1	26-04-2000 13-04-2000 16-08-2001 20-08-2002 13-04-2000
WO 0001588 A	13-01-2000	US 6250234 B1 US 6283044 B1 AU 4831799 A BR 9911746 A CA 2336484 A1 CN 1314860 T CZ 20004905 A3 EP 1115622 A1 HU 0102819 A2 JP 2002519258 T PL 346761 A1 TR 200100627 T2 TW 407125 B WO 0001588 A1 US 2002134284 A1 US 2002043184 A1 US 2002011195 A1	26-06-2001 04-09-2001 24-01-2000 03-04-2001 13-01-2000 26-09-2001 17-04-2002 18-07-2001 28-11-2001 02-07-2002 25-02-2002 23-07-2001 01-10-2000 13-01-2000 26-09-2002 18-04-2002 31-01-2002

THIS PAGE BLANK (USPTO)